

Specifications

PopUp WiFi GO HD

Compact, powerful, high-availability WiFi unit with external ethernet port and battery compatibility.

QUICK FACTS

- Runs using multiple 4G providers at once for increased performance and 99.9% uptime.
- Fibre and Cable WAN compatible.
- CAPTIVATE marketing integration compatible.
- Crowd counting and presence-analytics reporting available. [Quote on request].
- GPS Tracking available.



DIMENSIONS

- 31 x 27 x 20 cm
- 5kg

ROUTER

- Multi-provider capable [1 x Telstra 1 x Optus]
- 200Mbps throughput
- 8 Load-balancing algorithms
- Static IP capable
- Cloud-managed
- Medium-gain antennas for high 4G performance
- VLAN Priority capable
- 1 X Ethernet port for external switching or WAN connectivity
- WiFi WAN compatible

POWER

- Powered by standard Australian power plug
- Battery power available via external 4 pin XLR connector [12V DC]
- Low power consumption [approx. 20 watts]
- Compatible with generators
- Tested and tagged

ACCESS POINT

- 50 concurrent users
- 802.11AX
- CAPTIVATE compatible
- 4x4 MIMO
- 5Ghz and 2.4Ghz [5Ghz recommended]
- Complies with all main WiFi security standards
- Web content filtering

BUILD

- Rugged hard case construction
- Splash resistant
- Approved to take as carry-on or checked baggage on planes.
- Locked, can be opened by airport security [TSA approved]
- 4 pin XLR power inlet to connect to battery power
- Green power indicator light
- External Ethernet – CAT6A for connecting a network switch, direct client access or external WAN